

VI-N6120

Multi-Purpose No Residue Polyethylene Vinyl Tape

VI-N6120 is one of our most popular adhesive tapes due to its versatility and consistent performance. Used extensively by both stucco and abatement contractors, it is a staple product in our Construction product line. Made from an extra strength polyethylene film, it is coated with a high tack synthetic rubber adhesive that leaves no residue when removed from most surfaces within 7-10 days. It is widely used for stucco masking, temporary holding and general repairs.

Application

- Use to hang polyethylene films for mold and asbestos remediation & demolition (i.e. for containment rooms and clean rooms)
- Use to seam polyethylene film for under the slab vapor barriers
- Use to mask windows and doors in stucco applications
- Use to splice polyethylene films during manufacturing
- Use for color-coding and floor marking for exhibits and sporting events

Features & Benefits

- High tack adhesive bonds well to most surfaces over a wide temperature range
- Excellent low-temperature bonding
- Tough, flexible and conforms well in corners
- Leaves little to no residue upon removal from most surfaces within 7-10 days



- Waterproof backing
- Maintains a watertight seal in all weather conditions when properly applied
- Hangs and tears straight, is curl resistant and has an easy unwind
- Holds strong which prevents lifting
- Hand tearable making it easy to use
- Does not curl or splinter making it easy to apply

Storage & Usage Conditions

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

Sizes

1.89 in x 60 yd | 48mm x 55m

2.83 in x 60 yd | 72mm x 55m

Technical Data

Carrier	Polyethylene Film
Adhesive	Synthetic Rubber
Total Thickness	7 mils
Tensile	18 lbs/in
Adhesion	60 oz/in
Elongation	80%



Permeability Rating (ASTM F-1249)	0.357200 g/sq. m/d 0.023045 g/100 sq. in/d
Colors	Blue, Black, Red, White, Transparent

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved to be defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.